

### Characteristics

$I_F$	2	A
$V_{RRM}$	50~800	V
$I_{FSM}$	100	A
$V_F$	0.95~1.85	V

### Features


- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge current capability
- Super fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

### Mechanical Data


- Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Polarity: Cathode line denotes the cathode end

### Package Outline Dimensions

#### SMB



Dimensions in inches and millimeters



### Maximum Ratings & Electrical Characteristic

$T_a=25^\circ\text{C}$  unless otherwise specified


	Symbol	ES2AB	ES2BB	ES2DB	ES2GB	ES2JB	ES2KB	UNITS
Marking Code	-	ES2AB	ES2BB	ES2DB	ES2GB	ES2JB	ES2KB	-
Max. Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	Volts
Max. RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	Volts
Max. DC blocking Voltage	$V_{DC}$	50	100	200	400	600	800	Volts
Average rectified output current @60Hz sine wave, Resistance load, TL (Fig.1)	$I_o$	2.0						Amps
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, $T_j=25^\circ\text{C}$	$I_{FSM}$	50.0						Amps
Forward voltage at 2.0A	$V_F$	0.95		1.30		1.70	1.85	Volts
Maximum DC reverse current at rated DC blocking voltage per diode @ $V_{RM}=V_{RRM}$	$T_a=25^\circ\text{C}$	5						$\mu\text{A}$
	$T_a=125^\circ\text{C}$	100						
Typical thermal resistance (1)	$R_{\theta J-A}$	60						$^\circ\text{C/W}$
	$R_{\theta J-L}$	22						
Maximum reverse recovery time $I_F=0.5\text{A}$ , $I_R=1.0\text{A}$ , $I_{rr}=0.25\text{A}$	$T_{RR}$	35						nS
Operating junction and storage temperature range	$T_J, T_{STG}$	-55 to +150						$^\circ\text{C}$

Notes:


- (1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.3"x0.3" (8.0mmx8.0 mm) copper pad areas

### Rating and Characteristics Curves


**Fig. 1  $I_o$ -TL Curve**




**Fig. 2 Forward Surge Current Capability**




**Fig. 3 Typical Forward Characteristics**




**Fig. 4 Typical Reverse Characteristics**



**Fig. 5 Diagram of circuit and Testing wave form of reverse recovery time**






- NOTES:  
1. Rise Time=7ns max .Inpot Impedance=1M Ω 22pf  
2. Rise Time=10ns max.Source Impedance=50 Ω



### Packaging Specifications


Package	A0 (mm)	B0 (mm)	K0 (mm)	D0 (mm)	E (mm)	F (mm)	P0 (mm)	P1 (mm)	P2 (mm)	T (mm)	W (mm)
SMA	2.8±0.1	5.33±0.1	2.36±0.1	1.55±0.1	1.75±0.1	5.50±0.1	4.0±0.1	4.0±0.01	2±0.1	0.25±0.1	9.4±0.1
SMB	3.8±0.1	5.40±0.1	2.45±0.1	1.55±0.1	1.75±0.1	5.50±0.1	4.0±0.1	8.0±0.01	2±0.1	0.25±0.1	9.4±0.1
SMC	6.05±0.1	8.31±0.1	2.54±0.1	1.55±0.1	1.75±0.1	7.50±0.1	4.0±0.1	8.0±0.05	2±0.1	0.25±0.1	12±0.1



Package	D1 (mm)	D0 (mm)	W1 (mm)	D (mm)
SMA	75	13.5	13.5	330
SMB	75	13.5	13.5	330
SMC	75	13.5	17.0	330


NOTE : The tolerance of reel is ±2mm

### Suggested Pad Layout



Unit: inches(millimeters)

### Recommmend IR Reflow Soldering Thermal Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (Tsmin)	150°C
Temperature Max. (Tsmax)	200°C
Time (ts) from (Tsmin to Tsmax)	60-120 seconds
Average Ramp-up Rate (tL to tP)	3°C/second max.
Liquidous Temperature (TL)	217°C
Time (tL) Maintained Above (TL)	60 – 150 seconds
Peak Temperature	260°C +0°C / -5°C
Time (tP) within 5°C of actual Peak Temperature	30 seconds
Ramp-down Rate (TP to TL)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.

### Ordering Information

Part Number	Description	Quantity
ES2AB-ES2KB	SMB Reel	3000 pcs

### DISCLAIMER

- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Paceleader, Paceleader reserve the right to make changes to the information in this document.
- Though Paceleader make effort to improve product quality and reliability, Product can malfunction and fail due to their inherent electrical sensitivity and vulnerability to physical stress, it is the responsibility of the customer, when utilizing Paceleader products, to comply with the standards of safety in making a safe design for entire system and to avoid situation in which a malfunction or failure., In developing a new designs, customer should ensure that the device which shown in this documents are used within specified operating ranges.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Paceleader for any infringements of patents or other rights of the third parties which may result from its use.